

	Type	Connection End	Watt	Kg	Diameter range in mm																					
					4	5	6	8	10	12	14	16	18	20	22	24	25	26	28	30	32	35	37	40		
Battery Hammer	TE6-A	TE-C	375	4.7	140 (570)																					
Rotary Hammers	TE2-M	TE-C	600	2.6		120 (500)																				
	TE6-C	TE-C	650	2.5			120 (500)				90 (360)															
	TE15-C	TE-C	710	3.9				60 (280)																		
	TE16-C	TE-C	800	3.9				70 (270)				40 (160)														
Combihammers	TE35	TE-T	830	4.9						150 (640)			80 (320)													
	TE56-ATC	TE-Y	1100	6.6								50 (190)														
	TE76-ATC	TE-Y	1300	7.9									25 (100)							15 (60)						
	Type		Watt	Kg	Size of opening in mm																					
Breakers	TE76-ATC	TE-Y	1300	7.9	312 x 312 x 100					(634 x 634 x 100)																
	TE706-AVR	TE-Y	1200	7.2	630 x 630 x 100					(1265 x 1265 x 100)					Wall application											
	TE905-AVR	TE-S	1600	11.3	500 x 500 x 100					(1190 x 1190 x 100)					Floor application											

Drilling into concrete / masonry

optimum

possible

1st number is based on 2.5m/sec².
(Second number) is based on 5m/sec².

Right tool for the job: The Hilti Product Selector.