Victorian schools

Victorian schools typically have good daylighting and high ceilings, which give them great potential for adaptation. Their weakness is usually their circulation and WCs, which are difficult to correct owing to their heavy load-bearing masonry structure. Some may also have listed status. Specific fabric problems that might need to be dealt with in a Victorian school refurbishment include:

	Typical repair and alteration items	Cost range
Alterations	Forming openings in solid masonry w	all £550 to £650 each
Upper floors	Rot to joists or floorboards: repairs to	o £40 to £50
	affected timber joists including lifting and re-fixing floorboards	g per joist
Roof	Rot or infestation of timber roof	£70 to £80
	members, spread of rafters: isolated repairs and strengthening	per metre
	Nail sickness in slate roof: re-drill	£50 to £60
	and re-fix slates	per 10 slates
	Slate delamination: replace	£70 to £80 per 10 slates
	Lead work weathering: replace	£70 to £80
	and wedge in lead flashings	per metre
	Parapet failure: reset, repoint and	£180 to £200
	provide lead capping	per metre
External walls	Solid wall failures: repoint, replace	£70 to £100
	spalling brickwork, close cracks (full	per square metre
	repointing and allowance for isolated	repair)
	DPC failure: chemical injected DPC	£60 to £90
		per metre
Windows and	Potential for rot to external timber	£100 to
external doors	including window frames, gable end	£150 per
	louvres, etc: splice repairs or replacement	splice
Water	Amend layout to remove long dead	£45 to £60
	legs and add trace heating	per metre

Rates are current in third quarter 2010 based on an average UK location; procurement based on works done on a call-off basis by individual specialist contractors. They include preliminaries, overhead and profit and disposal of materials, but exclude the costs of specialist access where required. Professional fees and VAT are also excluded.